












Klebeband-Guide

Produkt	Klebekraft (Adhäsion) 	Scherfestig- keit (Kohäsion) 	Anfangs- haftung (Tack) 	Preis/ Leistung 	Leise Abrollung 	Wärme- beständig- keit 	Kälte- beständig- keit 	Packung über 25 kg 	Raue Karton- Oberfläche 	Automaten- tauglich 	Empfohlenes Abrollgerät 
OPP 430	e	ee	e	e	eee	eee	ee	e	e	e	HST, H-CP
OPP 440	ee	ee	e	e	eee	eee	ee	ee	ee	e	HST, H-CP
OPP 230	eee	e	eee	ee		e		e	e	eee	ND 2990
OPP 235	eee	e	eee	e		e		ee	e	eee	ND 2990
OPP 330	ee	eee	e	ee		e	e	e	eee	ee	HST, H-CP
OPP 335	ee	eee	ee	e		e	ee	ee	eee	ee	HST, H-CP
PVC 100	ee	eee	ee	e	ee	e	ee	eee	eee	e	HST, H-CP
PVC 140	eee	eee	ee	e	ee	e	ee	eee	eee		HST, H-CP
PVC 170	eee	eee	ee	e	ee	e	ee	eee	eee		HST, H-CP